NEW

R1234YF + R134A
AIR CONDITIONING RECHARGE KIT
ONE REFRIGERANT / ONE HOSE / ALL AUTOMOTIVE APPLICATIONS
EACH CAN REPLACES 12OZ R1234YF - 17OZ R134A - 19OZ R12

PART NUMBER
AR4247RT



Included
2 - Cans Leak Resistant Design Refrigerant
1 - Installation Hose
2 - Adapters (R134a/R1234yf)



AR4247
Large Molecule Leak Resistant Design Refrigerant



R1234yf
(Adapter)



R134a
(Adapter)



AR4252LYF
(Adapters + Hose)

KEY FEATURES

- **Dual Refrigerant Compatibility**
  Services both R1234yf and R134a A/C systems with one convenient kit.
- **One Kit, Multiple Applications**
  Ideal for domestic and import vehicles, covering a wide range of model years.
- **Complete Recharge Solution**
  Includes 2 cans leak resistant design refrigerant, 1 installation hose, and 2 adapters — everything needed to recharge.
- **Quick & Easy Installation**
  Simple hose and adapter setup reduces service time and complexity.
- **Leak-Safe Connections**
  Secure fittings help minimize refrigerant loss during charging.
- **Restores Cooling Performance**
  Helps deliver colder air output and improved A/C efficiency.
- **Compact & Portable**
  Easy to store and transport — perfect for shops, mobile techs, or emergency use.
- **Professional-Grade Aftermarket Quality**
  Built to meet the demands of real-world automotive service environments.
- **LARGE MOLECULE LEAK RESISTANT DESIGN REFRIGERANT**

PN: AR4247RT

FMSI EDELMANN FITTINGS

PROBLEM SOLVING AUTOMOTIVE HARDWARE

KOOL-AIR

REPLA 134 1234YF

EACH CAN REPLACES

12OZ R1234YF - 17OZ R134A - 19OZ R12

KOOL-AIR

REPLA 134 1234YF

REFRIGERANT / RÉFRIGÉRANT

EACH 6 OUNCE 170 GRAM CAN OF REPLA 134/1234YF REPLACES
19 OUNCES OF R12 17 OUNCES OF R134A 12 OUNCES OF R1234YF

CHAQUE CANETTE DE 170 GRAMMES (6 ONCES) DE REPLA 134/1234YF REMPLACE
19 ONCES DE R12 17 ONCES DE R134A 12 ONCES DE R1234YF

AUTOMOTIVE - TRUCKING/REEFER UNITS - AGRICULTURE
L'AUTOMOBILE - LE CAMIONNAGE ET L'AGRICULTURE

- RUNS COLDER THAN R1234YF - R134A - R12
- COMPATIBLE WITH PAG, ESTER, MINERAL, PRO PAO AND ROCK OILS

- PLUS FROID QUE LE R1234YF - R134A - R12
- FANCTIONNE AVEC LES HUILES DE PAG, ESTER, MINERAL, PRO PAO ETROCK OILS

THIS END UP FOR CHARGING
CE CÔTE EN HAUT POUR REMPLISSAGE

DANGER
FLAMMABLE/ INFLAMMABLE
IRRITANT
CONTENTS UNDER PRESSURE/
CONTENU SOUS PRESSION

NET WEIGHT/POIDS NET: 6OZ (170G)

DIRECTIONS FOR USE

1. Locate low side Air Conditioning port (larger of two AC lines) blue or black cap. 2. Attach the installation/re-charge hose can tap to the REPLA 134/1234yf thread on can. Connect quick coupler end of hose to the low side port on the vehicle. 3. Thread can tap clockwise to pierce can then thread counterclockwise to allow refrigerant to flow into vehicle. 4. Start the engine and turn AC controls to max. 5. Invert the can and let the refrigerant flow into the vehicle. Do not overcharge refrigerant. 6. Monitor the gauge (ideal pressure is 28-35psi) test vents inside vehicle to confirm it is blowing cold.

DO NOT OVERCHARGE!

Exceeding 414 KPA (60psi) on low side may damage compressor. In some cases, clearing the site glass overcharges the unit. Any overcharging may cause loss of cooling efficiency.

CONTENTS MAY CATCH FIRE. MAY IRRITATE EYES. MAY IRRITATE SKIN. CONTAINER MAY EXPLODE IF HEATED. Do not smoke. Use only in a well-ventilated area. Keep away from flames, such as pilot light, and any object that sparks, such as an electric motor. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Do not puncture. Do not burn. Store away from heat.
FIRST AID: Contains Naphtha (petroleum) heavy distillates and R290 propane. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

CONSUMER COMMODITY • MADE IN CHINA • R290 GAS

MODE D'EMPLOI

1. Repérez le port de climatisation côté basse pression (le plus grand des deux tuyaux de climatisation) avec le capuchon bleu ou noir.2. Fixez le robinet du tuyau d'installation/de recharge aux filets de la cannette REPLA 134/1234yf. Raccordez l'extrémité du tuyau munie d'un raccord rapide à l'orifice basse pression du véhicule. 3. Vissez l'adaptateur fileté dans le sens horaire pour percer la cannette, puis dévissé dans le sens antihoraire pour permettre au réfrigérant de circuler dans le véhicule. 4. Démarrez le moteur et réglez les commandes de la climatisation au maximum. 5. Retournez la cannette et laissez le réfrigérant s'écouler dans le véhicule. Ne remplissez pas trop le réfrigérant. 6. Surveillez le manomètre (la pression idéale est de 28 à 35 psi) et testez les bouches d'aération à l'intérieur du véhicule pour confirmer qu'il souffle de l'air froid.

NE SURCHARGEZ PAS LE CIRCUIT!

LE CONTENU PEUT S'ENFLAMMER. PEUT IRRITER LES YEUX. PEUT IRRITER LA PEAU. CE CONTENANT PEUT EXPLOSER S'IL EST CHAUFFÉ. Ne pas fumer. N'utiliser que dans un endroit bien aéré. Tenir loin des flam-mes, telle une flammes pilote, et de tout objet produisant des étincelles, tel un moteur électrique. Éviter tout contact avec les yeux. Éviter tout contact avec la peau ou les vêtements. Tenir hors de la portée des enfants. Ne pas perforer. Ne pas brûler. Conserver loin des sources de chaleur.
PREMIERS SOINS: Contient Naphta lourd (pétrole) distillat et R290 propane. En cas d'ingestion, appeler immédiatement un centre antipoison ou un médecin. Ne pas provoquer le vomissement. En cas de contact avec les yeux, rincer avec de l'eau pendant 15 minutes. En cas de contact avec la peau, bien rincer avec de l'eau.

PRODUIT DE CONSOMMATION • FABRIQUÉ EN CHINE • GAZ R290

8 06416 64247 2

FMSI EDELMANN FITTINGS
PROBLEM SOLVING AUTOMOTIVE HARDWARE

BURLINGTON, ON L7L 6A6
FMSIINC.COM

PART NUMBER

AR4247RT

WATCH INSTRUCTIONS BEFORE USE